

# BENNETT SAFETYWEAR LTD

MERSEY ROAD, CROSBY, LIVERPOOL, L23 3AF, UK  
TEL: +44 (0)151-924-3996 FAX: +44 (0)151-924-6548  
Web site : <http://www.bennettsafetywear.co.uk>  
Email : sales@bennettsafetywear.co.uk

## EXCAVATOR™-K

EXCAVATOR™-K – a new addition to the range of gloves for the emergency services from Bennett Safetywear Ltd, European market leader in the manufacture of high performance hand protection for police, military, fire fighting and industrial applications.

The EXCAVATOR™-K combines environmentally sourced and the latest technologically advanced materials to offer superior levels of protection against mechanical risks, together with exceptional dexterity and flexibility.

### FEATURES AND BENEFITS

- ❖ Kangaroo leather outer which :
  - is widely recognised as being one of the strongest lightweight leathers available
  - retains 8 times more of its original strength than bovine leather (cowhide) when processed
  - is selected from non-endangered species culled for environmental purposes
  - avoids environmental issues associated with cattle rearing
  - has a water-resistant treatment
- ❖ Maximum protection against most mechanical hazards, including level 5 cut-resistance (see below)
- ❖ Seamless lightweight composite fibre liner
- ❖ Withstands 30 seconds @ 100°C
- ❖ Reinforced thumb crotch



- ❖ Elasticated wrist with Kangaroo leather vein patch front and back
- ❖ Dark brown finish as standard; other colours subject to minimum order quantities
- ❖ Sewn with aramid thread throughout
- ❖ Maximum dexterity and tactility according to EN 420
- ❖ Optional waterproof membrane for enhanced resistance to water, chemicals and blood-borne pathogens (Minimum order quantities will apply)
- ❖ Wide size range : XS:S:M:L:XL (others sizes on request)
- ❖ BS EN ISO 9001 : 2000 quality control system

### PERFORMANCE DATA

#### TESTS

Abrasion resistance :	3	EN388 : 2003
Blade cut resistance :	5 *	EN388 : 2003
Tear resistance :	4 *	EN388 : 2003
Puncture resistance :	4 *	EN388 : 2003
Dexterity :	5 *	EN420 : 2003
Contact heat :	1	EN407 : 2003

\* Maximum obtainable

### APPLICATIONS

- ❖ Technical rescue
- ❖ RTC's
- ❖ Mechanical hazard handling